


# OLYMPIAN™

## GEP50-5

*Diesel Generator Set  
Exclusively from your Caterpillar® dealer*



Output Ratings		
Generating Set Model	Prime*	Standby*
380-415V, 50Hz	45.0 kVA 36.0 kW	50.0 kVA 40.0 kW
480V, 60 Hz	50.0 kVA 40.0 kW	56.3 kVA 45.0 kW

\* Refer to ratings definitions on page 4.  
Ratings at 0.8 power factor.

Technical Data		
Engine Make & Model:	Perkins 1103A-33TG1	
Alternator Model:	LL2014C	
Base Frame Type:	Heavy Duty Fabricated Steel	
Circuit Breaker Type:	3 Pole MCB	
Frequency:	50 Hz	60 Hz
Engine Speed: RPM	1500	1800
Fuel Tank Capacity: litres (US gal)	175 (46.2)	
Fuel Consumption, Prime: l/hr (US gal/hr)	10.6 (2.8)	11.9 (3.1)
Fuel Consumption, Standby : l/hr (US gal/hr)	11.9 (3.1)	13.5 (3.6)

# Engine Technical Data

Physical Data	
Manufacturer:	Perkins
Model:	1103A-33TG1
No. of Cylinders/Alignment:	3 / In Line
Cycle:	4 Stroke
Induction:	Turbocharged
Cooling Method:	Water
Governing Type:	Mechanical
Governing Class:	ISO 8528 G2
Compression Ratio:	17.25:1
Displacement: l (cu.in)	3.3 (201.4)
Bore/Stroke: mm (in)	105.0 (4.1)/127.0 (5.0)
Moment of Inertia: kg m <sup>2</sup> (lb. in <sup>2</sup> )	1.14 (3896)
Engine Electrical System:	
-Voltage/Ground:	12/Negative
-Battery Charger Amps:	65
Weight: kg (lb) - Dry:	420 (926)
- Wet:	438 (966)

Air System	50 Hz	60 Hz
Air Filter Type:	Replaceable Element	
Combustion Air Flow:		
m <sup>3</sup> /min (cfm)	-Standby: 2.8 (99)	3.4 (120)
	-Prime: 2.6 (92)	3.2 (113)
Max. Combustion Air Intake		
Restriction: kPa (in H <sub>2</sub> O)	8.0 (32.1)	8.0 (32.1)
Radiator Cooling Air Flow:		
m <sup>3</sup> /min (cfm)	86.4 (3051)	105.6 (3729)
External Restriction to		
Cooling Air Flow: Pa (in H <sub>2</sub> O)	120 (0.5)	120 (0.5)

Cooling System	50 Hz	60 Hz
Cooling System Capacity:		
l (US gal)	10.2 (2.7)	10.2 (2.7)
Water Pump Type:	Centrifugal	
Heat Rejected to Water & Lube Oil: kW (Btu/min)		
-Standby:	30.6 (1740)	33.1 (1882)
-Prime:	26.1 (1484)	29.5 (1678)
Heat Radiation to Room:		
kW (Btu/min)	-Standby: 14.0 (796)	15.3 (870)
	-Prime: 11.9 (677)	13.0 (739)
Radiator Fan Load: kW (hp)	0.5 (0.7)	0.9 (1.2)
Cooling system designed to operate in ambient conditions up to 50°C (122°F). Contact your local Olympian dealer for power ratings at specific site conditions.		

Lubrication system	
Oil Filter Type:	Spin-On, Full Flow
Total Oil Capacity l (US gal):	8.3 (2.2)
Oil Pan l (US gal):	7.8 (2.1)
Oil Type:	AP1 CG4 15W-40
Cooling Method:	Water

Performance	50 Hz	60 Hz
Engine Speed: RPM	1500	1800
Gross Engine Power: kW (hp)		
-Standby:	46.4 (62.0)	55.6 (75.0)
-Prime:	42.2 (57.0)	50.5 (68.0)
BMEP: kPa (psi)		
-Standby:	1125.0 (163.2)	1124.0 (163.0)
-Prime:	1023.0 (148.4)	1020.0 (148.0)
Regenerative Power: kW	7.0	9.0

Fuel System				
Fuel Filter Type:	Replaceable Element			
Recommended Fuel:	Class A2 Diesel			
Fuel Consumption: l/hr (US gal/hr)				
	110% Load	100% Load	75% Load	50% Load
Prime				
50 Hz	11.9 (3.1)	10.6 (2.8)	7.9 (2.1)	5.6 (1.5)
60 Hz	13.5 (3.6)	11.9 (3.1)	9.1 (2.4)	6.7 (1.8)
Standby				
50 Hz		11.9 (3.1)	8.8 (2.3)	6.1 (1.6)
60 Hz		13.5 (3.6)	10.1 (2.7)	7.3 (1.9)
(based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)				

Exhaust System	50 Hz	60 Hz
Silencer Type:	Level 1	
Silencer Noise Reduction	SD80 (1)	
Pressure Drop Across		
Silencer System: kPa (in Hg)	0.82 (0.242)	1.08 (0.319)
Silencer Noise Reduction		
Level: dB	20	18
Max. Allowable Back		
Pressure: kPa (in. Hg)	10.0 (3.0)	15.0 (4.4)
Exhaust Gas Flow:		
m <sup>3</sup> /min (cfm)	-Standby: 7.7 (272)	9.6 (339)
	-Prime: 7.0 (247)	8.8 (311)
Exhaust Gas Temperature: °C (°F)		
m <sup>3</sup> /min (cfm)	-Standby: 540 (1004)	553 (1027)
	-Prime: 489 (912)	506 (943)

## Alternator Performance Data

Data Item	50 Hz				60 Hz				
	415/240V	400/230V 230/115V 200/115V	380/220V 220/110V	220/127V	480/277V 240/139V	380/220V 220/110V	240/120V 208/120V	230/115V	440/254V 220/127V
<b>Motor Starting Capability* kVA</b>	89	84	76	99	98	65	76	71	84
<b>Short Circuit Capacity** %</b>	300	300	300	300	300	300	300	300	300
<b>Reactances: Per Unit</b>									
<b>Xd</b>	2.660	2.870	3.180	2.370	2.650	4.230	3.530	3.820	3.160
<b>X'd</b>	0.120	0.130	0.140	0.100	0.120	0.190	0.160	0.170	0.140
<b>X''d</b>	0.059	0.063	0.070	0.052	0.059	0.093	0.078	0.084	0.070

Reactances shown are applicable to standby ratings.

\* Based on 30% voltage dip. Improved motor starting capability is available with optional Permanent Magnet generator or AREP excitation.

\*\* With optional Permanent Magnet generator or AREP excitation.

## Alternator Technical Data

Physical Data	
<b>Manufacturer:</b>	OLYMPIAN
<b>Model:</b>	LL2014C
<b>No. of Bearings:</b>	1
<b>Insulation Class:</b>	H
<b>Winding Pitch - Code:</b>	2/3 - 6
<b>Wires:</b>	12
<b>Ingress Protection Rating:</b>	IP23
<b>Excitation System:</b>	SHUNT
<b>AVR Model:</b>	R250

Operating Data	
<b>Overspeed: RPM</b>	2250
<b>Voltage Regulation (steady state) (%):</b>	+/- 0.5
<b>Wave Form NEMA = TIF:</b>	50
<b>Wave Form IEC = THF:</b>	2.0%
<b>Total Harmonic Content LL/LN:</b>	4.0%
<b>Radio Interference:</b>	Suppression is in line with European Standard EN61000-6
<b>Radiant Heat: kW (Btu/min)</b>	
-50 Hz:	5.8 (330)
-60 Hz:	6.6 (375)

Consult your Olympian representative for more information

## Technical Data

### 3 Phase Ratings and Performance at 50 Hz, 1500 RPM

Voltage	Prime		Standby	
	kVA	kW	kVA	kW
415/240V	45.0	36.0	50.0	40.0
400/230V	45.0	36.0	50.0	40.0
380/220V	45.0	36.0	49.8	39.8
230/115V	45.0	36.0	50.0	40.0
220/127V	45.0	36.0	50.0	40.0
220/110V	45.0	36.0	49.8	39.8
200/115V	45.0	36.0	50.0	40.0



### 3 Phase Ratings and Performance at 60 Hz, 1500 RPM

Voltage	Prime		Standby	
	kVA	kW	kVA	kW
480/277V	50.0	40.0	56.3	45.0
220/127V	50.0	40.0	56.3	45.0
380/220V	50.0	40.0	56.3	45.0
240/120V	50.0	40.0	56.3	45.0
230/115V	50.0	40.0	56.3	45.0
440/254V	50.0	40.0	56.3	45.0
220/110V	50.0	40.0	56.3	45.0
208/120V	50.0	40.0	56.3	45.0
240/139V	50.0	40.0	56.3	45.0

## Weights & Dimensions

Weights: kg (lb)	
Net (+ lube oil)	874 (1927)
Wet (+ lube oil & coolant)	884 (1949)
Fuel, lube oil & coolant	1032 (2275)

Dimensions: mm (in)	
Length	2150 (84.6)
Width	752 (29.6)
Height	1366 (53.8)



**Note:** General configuration not to be used for installation. See general dimension drawings for detail.

## Definitions

### Standby Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

### Prime Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

### Standard Reference Conditions

Note: Standard reference conditions 27°C (80°F) air Inlet Temp, 152.4m (500ft) A.S.L. 60% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

## General Data

### Documents

Operation and maintenance manuals provided.  
Wiring diagrams included.

### Quality Standards

BS4999, BS5000, BSEN60034, BSEN61000, IEC60034.

### Warranty

All equipment carried full manufacturer's warranty.

Information contained in this publication may be considered confidential.  
Discretion is recommended when distributing.

www.CAT-ElectricPower.com

Market: International  
LEHF5245-03

Materials and specifications are subject to change without notice.  
CAT, CATERPILLAR, OLYMPIAN, their respective logos and "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

© 2008 Caterpillar  
All rights reserved.  
Printed in U.S.A.